

## SYRDM5

## HF Mini Proximity Reader

### Feature

- Two-colors LED visual indication.
- Built-in Anti-Tamper protection.
- Communication :  
RS485 , Wiegand 26,32,34 bits.
- Built-in Watchdog to prevent system from halting.
- Built-in Buzzer.
- Card Compatibility :  
ISO14443A/B / 15693 / Mifare



### Specification

Specs/Item	SYRDM5-H1
Transmit Frequency	13.56MHz (Mifare)
Read Range	1 ~ 3 cm
Baud Rate	19,200 bps (4,800~115,200 bps)
Card Compatibility	ISO14443A/B/15693/Mifare
LED Indicator	1 LED
Communication	RS485 , Wiegand 26,32,34 bits
Anti-Tamper Facility	Built-in
Beep Tone	Built-in Buzzer
Operating Temperature	-20°C ~ +70°C
Input Voltage	8V~15V DC / 0.5~2W
Dimensions (W x H x D)	44 x 81 x 16.6 mm

❖ This specification is preliminary and subject to change without prior notice.

### Ordering Information

Item	Type
SYRDM5-W-H1	HF Mini Proximity Reader

### Proximity Mini



Copyright © 2013 SYRIS Technology Corp.

SYRIS  
ACCESS Reader  
SYRIS Security System