V8 device Firmware upgrade

1. Open Firmware upgrade tool "V8FirmwareTools_V0xxx.exe" (Download from Web)

<u>File L</u> anguage <u>A</u> bout						
Select firmware file						
File:	Model:					
1. <u>S</u>	1. <u>S</u> elect firmware file					
COM	ID: 0	Þ				
Port COM1	🔽 Verify 🔲 Skip error					
Speed: 19200,e,8,1	▼ V4/V5/V6 □ S/N	PIN: 0000				
19200,e,8,1 115200,n,8,1	Model: S/N:	ID:				
	Name: VER: VER:	ISP:				
Program/Download						
Venily check						
2. <u>U</u> pgrade						

2. Select SYB firmware file (ex. SYTD2N-U1_V0853_20200107.SYB)

🖸 開啟				×
搜尋位置(I):	SY86N_Tool:	s 🗸	🍅 🖻 🔿 🛛	
快速存取	curl-7.58.0 OLD SYTD2N-U1	_V0853_20200107.SYB		
レ 本機 <i>例</i> 路				
	檔案名稱(N): 檔案類型(T):	SYTD2N-U1_V0853_20200107. Firmware files (*.SYB)	SYB 🔹	開啟(Q) 取消

J_{1} induce the address and upgrade with the connection (1.5-	3. F	Find device IP	address and	d upgrade with	TCP connection	(RJ-45
--	------	----------------	-------------	----------------	----------------	--------

🔒 NET	Discover Version 1	.1		×
NUM	IP	MAC	INFO	Discover
8	192.168.1.191	AC:A2:13:B6:14:35	HLK-RM04(V1.78(Jul 23 2013))	
7	192.168.1.206	44:33:4C:C4:8A:27	HLK-RM04(V1.95(May 9 2014))	
6	192.168.1.192	AC:A2:13:B5:4B:C1	HLK-RM04(V1.78(Jul 23 2013))	
5	192.168.1.205	28:F3:66:A2:06:BF	SerialWiFi V3.24(190813153024)(M	
4	192.168.1.211	28:F3:66:A2:7C:0B	SerialWiFi V3.47(191106172941)(M	
3	192.168.1.212	28:F3:66:A2:6C:8B	SerialWiFi V3.24(190104181510)(M	
2	192.168.1.204	40:D6:3C:1F:91:B0	SerialWiFi V3.47(191106172941)(M	
1	192.168.1.189	28:F3:66:AF:DD:AD	SerialWiFi V3.24(190605163157)(M	

4. Upgrade. (Verify should be selected.)

🔞 V8 Firmware Upgrade Tools V0840 [2019-0)3-12]		_				
<u>F</u> ile <u>L</u> anguage <u>A</u> bout							
	Programming						
File: Desktop\SY86N_Tools\SYTC)2N-U1_V0853	Model:	SYTD2N-U1	VER: 0853			
1. <u>S</u> elect firmware file							
COM NET	ID: 0	•		Þ			
IP: 192.168.1.204	I	🗸 Verify	🗖 Skip error				
Port: 5001	l	□ \4/\5/\6	S/N	PIN: 0000			
	Model:	06C6	S/N: 20010001	ID: 0001			
	Name:	SYTD2NH	J VER: 0853	ISP: 0860			
Frogram/Download							
Verily shock							
2. <u>U</u> pgrade							

PS. If the upgrade fails, you can retry until successful. But do not restart the device or replug the power supply.

5. Upgrade OK

№ Firmware Upgrade Tools V0840 [2019-03-12] –						
<u>F</u> ile <u>L</u> anguage <u>A</u> bout						
Upgrade ok. O						
File: Desktop/SY86N_Tools/SYTD	2N-U1_V0853	vlodel: SYTD2N-U	J1 VER: 0853			
1. <u>S</u> elect firmware file						
COM NET	ID: 1		Þ			
IP: 192.168.1.101	🔽 Veri	ify 🗌 Skip er	rror			
Port: 5001	□ ∨4⁄	√5/√6 🗆 S/N	PIN: 0000			
	Model: 06C	6 S/N: 20010	001 ID: 0001			
	Name: Syn	D2N-UI VER:	ISP: 0860			
Program/Download						
Verify check						
2. <u>U</u> pgrade						

6. Open utility to check firmware version

🔞 V8 Command Tools V0855				– 🗆 X
<u>File Language About</u>				
COM NET				Close
IP: 192.168.1.204	▼ NET Search	Web Config Password =	dmin admin Port: 500	1 Connect
☑ Response ☐ ID 1	S/N 20010001	PID/CID: 00000000	CRC-16 CAES-128	3 Direct
COMMON COMM. DI/DO	READER CPU CARD	UHF UHF TID KEYPAI	D SY86/SY2 BT Card CA	RD LOG CONTRC
Get S/N	Model: 06C	6 SYTD2N-U1	S/N: 2001000	
Get ID	ID:	Special:	Set ID	ID: 1
Get Version	Name:	YTD2N-U1	F/W version: 0853	
Warm Start			FRAM:	FLASH:
Initial	NET Initial(10 Sec)	NET IP:101	NET DHCP	Memory